

Concrete grinder EBS 1802



Ø 125

Concrete grinder EBS 1802 SH



Ø 125

The powerful hand-held grinder for small to medium sized surfaces

USE:

- Grinding and smoothing of surfaces
- Removing of sceed seams, residual mud, plaster and coatings
- Preparing of surfaces, e.g. for tile renovation
- Concrete, screed, tile adhesive, plaster, paint, coatings, carpet adhesive – with special grinding wheels (accessories)

FEATURES:

- Powerful motor – high capacity
- Electronic – soft start, over current cut-off, optical overload indication

- The machine for every surface: PCD-grinding wheel with monobloc diamonds – high removal rate and long lasting
- Foldable front edge of dust guard – for grinding directly to the edge of the work area (no laborious reworking, saves time and costs)
- Brush rim – high suction power for dust-free working by connecting an industrial vacuum cleaner (accessory) to the 35 mm nozzle
- Parallel handle position – ergonomic handling allow exact and balanced guiding for a better surface finish
- Floor guiding device – available as accessory (not for use with PCD-grinding wheels)

SPECIFICATIONS	EBS 1802
Power input	1,800 W
Rated voltage	230 V ~
No-load speed	10,000 rpm
Disc Ø	125 mm
Spindle connection	Ø 22.2 mm
Weight	5.9 kg
Order no.	0633J000
Supplied	in a case with diamond-grinding wheel (concrete), tool kit

SPECIFICATIONS	EBS 1802 SH
Power input	1,800 W
Rated voltage	230 V ~
No-load speed	10,000 rpm
Disc Ø	125 mm
Spindle connection	Ø 22.2 mm
Weight	5.9 kg
Order no.	0633L000
Supplied	in a case with PCD-grinding wheel, tool kit

EBS 1802 SH – the machine for every surface: PCD-grinding wheel included in delivery

